


# DATA SHEET



## S6EXZ5311/292 Beamexpander

- magnification 1.0 - 3.0
- for 515 nm - 545 nm
- fused silica
- low absorption coating



outline drawing

# DATA SHEET



新特光电  
Sintec Optronics

## specifications

article number	S6EXZ5311/292
design wavelength [nm]	532
magnification factor	1.0 - 3.0 continuous
divergence adjustable <sup>1)</sup>	✓
optical principle	Galilei (no internal focus)
mounting thread	M30x1
pointing stability [mrad]	< 1
clear input aperture [mm]	10.5
clear output aperture [mm]	20.0
max. input beam diameter [mm]	9.0 (1x) - 6.0 (3x)
total number of lenses	4
total transmission [%]	97
lens material	fused silica
LIDT (coating) [J/cm <sup>2</sup> ]	2.5 (1ns pulse at 50Hz)
no internal ghosts [✓/✗]	✓
no internal ghosts, reversed usage	✗
weight [kg]	0.30
accessory	S6MEC0107 - adapter M30x1 to C-mount

## notes

1) Divergence is independent from magnification factor

Data given by design

Attention! The laser should not be operated while zooming!

LIDT = Laser Induced Damage Threshold, valid for the coating at design wavelength and gaussian intensity profil